

Technical Bulletin

MAYTAG®

Type Policy Letter
√ Service Information

Date: September 2006

No: TDL-0121-S
Page 1 of 1

Attention √ Service Managers
√ Service and Parts Managers


Models MAH6700AWM MAH6700AWW MAH8700AWM, MAH8700AWW
MAH9700AWM, MAH9700AWQ MAH9700AWW

Brand
Maytag

Issue Service Manuals, Tech Data Sheets and Schematic updates.

Product
Laundry

Warranty Standard product manufacturing warranty applies.



⚠ WARNING

Electrical Shock Hazard

Disconnect power before servicing.

Replace all parts and panels before operating.

Failure to do so can result in death or electrical shock.

Action

1. The suspended time in Hold Quick Spin Step is listed for each model below.
MAH9700AWW: 10 minutes
MAH8700AWW: **1 minute on early models** (Software was later changed to 10 minutes)
MAH6700AWW: 10 minutes

2. The **Output Test** for the fabric softener (MAH8700* and MAH9700* only)
The selector knob has to be on **Whites**, not **Colors** to activate the bleach and main cold valve.

3. Correct motor winding resistance readings is 3.0 ohms ($\pm 7\%$ at 20° C/68° F) for belt driven units.

MAH6700* and MAH8700* washers.



Normal resistance is approximately 3.0 ohms between any 2 pins (1,2 or 3) on motor connector.